VANRELY

Steel structures, steel coils and roofing sheets from China.

Stainless Steel Coil and Sheet

Cold-rolled and hot-rolled stainless steel in 200, 300 and 400 series, 2B / BA / No.4 / HL / mirror finishes.

View specs

Grade	201 (J1 / J2 / J4 — please specify), 202, 304, 304L, 316, 316L, 321, 310S, 430, 409L, 410, 2205 201 J-series (J1 / J2 / J4) are Chinese mill designations by copper content, not ASTM / EN grades. J1 ≈ 0.8% Cu, softer and easier to form; J2 ≈ 0.3% Cu, harder and cheaper.
Thickness	Cold-rolled 0.3–3.0 mm (0.1–6.0 mm on request); hot-rolled 3–100 mm Chinese mills quote by ACTUAL thickness. GB/T 3280 normal precision allows e.g. 1.0 mm nominal × 1219 mm to measure ≥0.9 mm. We state both nominal and actual thickness on the PI.
Width	1000 / 1219 / 1250 / 1500 mm standard; 1800 / 2000 mm for 304 on request; slitting available
Surface finish	2B (standard), BA, 2D, No.1 (hot-rolled), No.4, HL (hairline), No.8 mirror (8K) 2B = cold rolled, annealed, pickled and skin-passed (ASTM A480), Ra about 0.1–0.5 µm.
Coil inner diameter	508 mm or 610 mm
Coil weight	2–10 t (slit coils lighter)
Minimum order	26 t per order; sizes and colors can be mixed in one order
Lead time	7–15 days after deposit

Detailed specifications

Protection	PE / PVC protective film, paper interleaf
Edge	Mill edge or slit edge
Weight per m²	kg/m² = thickness (mm) × 7.93 (200 / 300 series) or × 7.75 (400 series)
Price basis	EXW / FOB / CIF / CFR
Quality documents	Mill test certificate (MTC) or factory quality certificate with every order

Packing and loading

Sheets on wooden pallets with film and edge protectors; coils strapped with waterproof wrapping

To quote, send

Grade, thickness, width, finish, quantity and destination port.

Guangdong Wanxin International Supply Chain Co., Ltd.

Room 905-A533, No. 26 Jinlong Road, Nansha District, Guangzhou, Guangdong, China

Phone / WeChat: +86 173 2988 2029 · WhatsApp: +86 173 2988 2029 · sales@vanrely.com

Mon–Sat, 9:00–18:00 China time (GMT+8)

vanrely.com

Updated: Oct 2026